

REF.
DATE

For each item select the request option



1

STOCKY 25

FOLIO®

Product type	Quantity	☐ 1 CCT	☐ 2 Lens	☐ 3 Dimmability	☐ 4 Aluminum finish
STOCKY 25					

[mm] [in]



LIGHT SOURCE

LED type:	Nichia
LED Voltage:	24 Vdc
LED Duration:	50 000 h.
Power:	20 W/m
Screen type:	☒ Opal Double-Satin
Delivered Lumen:	☒ 1500 lm/m
Efficacy:	75 lm/W
Candela:	510 cd
CRI:	> 90 (> 100 on request - Nichia Optisolis™)
R9:	> 50 (> 80 on request - Nichia Optisolis™)
TM30:	Rf: 91 Rg: 100
SDCM:	3
Color Temperature (CCT):	☐ 2700K ☐ 3000K ☐ 3500K ☐ 4000K ☐ 5700K ☐ on request: 2000K, 2200K, 2500K, 6500K

The Linear LED range redefines how light interacts with surfaces. Designed to meet the most demanding bespoke projects, these linear systems offer endless possibilities in terms of length, output, and placement. By sharing a common technical DNA with our point-source elements, they guarantee absolute visual harmony and a streamlined installation process, making them the ideal choice for comprehensive lighting layouts. Every detail is engineered to transform functional lighting into a distinctive architectural element.



GENERAL SPECS.

Dimensions:	21 x 26.7 mm / 0.82 x 1.05 in
Length:	max 3000 mm / 118 in (custom)
IP:	40

OPTICS

Optic Type:	lens
Beam Angle (BA°)	☐ 180° ($\angle$ 25°)

ELECTRICAL

Driver:	AC/DC 24 V
Dimmability:	☐ 0-10 V ☐ 1-10 V ☐ DALI ☐ DMX ☐ Bluetooth ☐ PUSH ☐ Casambi

Images / 3D / sections and the relative details shown in the following pages are generic and indicative. The number and position of the fixing points and fasteners may change during the production phase. The type, quantity and position of the Folio panels' power cables are indicative.



REF.
DATE

For each item select the request option

2

STOCKY 25

FOLIO®

Product type	Quantity	☐ 1 CCT	☐ 2 Lens	☐ 3 Dimmability	☐ 4 Aluminum finish
STOCKY 25					

ALUMINIUM FINISHES

☐ 4


RAL/NCS/Pantone:

Polished finish:



LENS INFO


Beam Angle (BA°): 180° ($\angle$ 25°)



INSTALLATION


Mechanic fastening

1. Install the fixing profile by screws
2. Snap the STOCKY profile into the fixing profile



Magnetic fastening

1. Fix the metal plate to the material
2. Snap the magnet to the metal plate




POWER CABLE EXIT

Power cable: 1000 mm / 39 in


OPTION .A
EXIT FROM THE END CAP



OPTION .B
EXIT FROM THE SIDE




OPTION .C
EXIT FROM BELOW




POSITION GUIDELINES

OPTION .A



OPTION .B



Images / 3D / sections and the relative details shown in the following pages are generic and indicative. The number and position of the fixing points and fasteners may change during the production phase. The type, quantity and position of the Folio panels' power cables are indicative.