



REF.
DATE

For each item select the request option



1

SLIM.9U

FOLIO®

Product type	Quantity	1 Power	2 Screen type	3 CCT	4 Lens	5 Dimmability	6 Aluminum finish
SLIM.9U							

[mm] [in]



LIGHT SOURCE

LED type:	186 LED/m (pitch 5,31mm)
LED Voltage:	24 Vdc
LED Duration:	50 000 h.
Power:	☐ 10 W/m ☐ 15 W/m
Screen type:	☐ Op15 ☐ Op25
Delivered Lumen:	☒ 10W/m 1254 lm/m (Op15), 1128 lm/m (Op25) ☒ 15W/m 1804 lm/m (Op15), 1623 lm/m (Op25)
Efficiency:	☒ 10W/m 125.4 lm/W (Op15), 112.8 lm/W (Op25) ☒ 15W/m 120.2 lm/W (Op15), 108.2 lm/W (Op25)
Candela:	☒ 10W/m 427 cd (Op15), 384 cd (Op25) ☒ 15W/m 614 cd (Op15), 552 cd (Op25)
CRI:	> 90
R9:	> 50 > 80
TM30:	Rf: 91 Rg: 100
SDCM:	2
Color Temperature (CCT):	☐ 2700K ☐ 3000K ☐ 3500K ☐ 4000K ☐ 5000K ☐ on request: 2000K, 2200K, 2500K, 6500K

The Linear LED range redefines how light interacts with surfaces. Designed to meet the most demanding bespoke projects, these linear systems offer endless possibilities in terms of length, output, and placement. By sharing a common technical DNA with our point-source elements, they guarantee absolute visual harmony and a streamlined installation process, making them the ideal choice for comprehensive lighting layouts. Every detail is engineered to transform functional lighting into a distinctive architectural element.



GENERAL SPECS.

Dimensions:	9 x 9 mm / 0.35 x 0.35 in
Length:	max 2000 mm / 78.7 in (custom)
IP:	40

OPTICS

Optic Type:	lens
Beam Angle (BA°)	☐ 120° ☐ 180°

ELECTRICAL

Driver:	AC/DC 24 V
Dimmability:	☐ 0-10 V ☐ 1-10 V ☐ DALI ☐ DMX ☐ Bluetooth ☐ PUSH ☐ Casambi

Images / 3D / sections and the relative details shown in the following pages are generic and indicative. The number and position of the fixing points and fasteners may change during the production phase. The type, quantity and position of the Folio panels' power cables are indicative.



REF.
DATE

For each item select the request option

2

SLIM.9U


FOLIO®

Product type	Quantity	1 Power	2 Screen type	3 CCT	4 Lens	5 Dimmability	6 Aluminum finish
SLIM.9U							

ALUMINIUM FINISHES


6

Color finish:



LENS INFO

Beam Angle (BA°): 120° ☐ 180° ☐




INSTALLATION

Magnetic fastening

1. Fix the metal plate to the material

2. Attach the linear light




POWER CABLE EXIT

Power cable: 1000 mm / 39 in


OPTION .A
EXIT FROM THE END CAP



OPTION .B
EXIT FROM THE SIDE




OPTION .C
EXIT FROM BELOW




POSITION GUIDELINES


OPTION .A



OPTION .B



OPTION .C



Images / 3D / sections and the relative details shown in the following pages are generic and indicative. The number and position of the fixing points and fasteners may change during the production phase. The type, quantity and position of the Folio panels' power cables are indicative.