

SLIM.9U

FOLIO

Product type	Quantity	1 Power	2 Screen type	3 CCT	4 Lens	5 Dimmability	6 Aluminum finish
SLIM.9U							

[mm] [in]





LIGHT SOURCE

LED Type:		Nichia
LED Duration:		50000 hours
Power: 1	☐	10 W/m / 3.05 W/ft std
	☐	15 W/m / 4.57 W/ft high
Screen Type: 2	☐	Opal 15 O15
	☐	Opal 25 O25
Delivered Lumen:	std O15	1254 lm/m / 382.22 lm/ft
	std O25	1128 lm/m / 343.81 lm/ft
	high O15	1804 lm/m / 549.86 lm/ft
(186 LED/m)	high O25	1623 lm/m / 494.69 lm/ft
Efficiency:	std O15	125.4 lm/W
	std O25	112.8 lm/W
	high O15	120.2 lm/W
	high O25	108.2 lm/W
CRI:		› 90
R9:		› 50
TM30:		Rf: 91 Rg: 100
SDCM:		3
Color Temperature (CCT): 3	☐	○ 2700K
	☐	○ 3000K
	☐	○ 3500K
	☐	○ 4000K
	☐	○ 5000K
	☐	on request: 2000K, 2200K, 2500K, 6500K

The Linear LED range redefines how light interacts with surfaces. Designed to meet the most demanding bespoke projects, these linear systems offer endless possibilities in terms of length, output, and placement. By sharing a common technical DNA with our point-source elements, they guarantee absolute visual harmony and a streamlined installation process, making them the ideal choice for comprehensive lighting layouts. Every detail is engineered to transform functional lighting into a distinctive architectural element.

GENERAL SPECS.

Dimensions:	9 x 9 mm / 0.35 x 0.35 in
Lenght:	max 2000 mm / 78.7 in

OPTICS

Optic Type:		lens
Beam Angle (BA°) 4	☐	120°
	☐	180°

ELECTRICAL

Voltage:		24 Vdc		
Class:		3		
Driver:		AC/DC 24V		
Dimmability: 5	☐	0-10 V	☐	PHASE
	☐	1-10 V	☐	PUSH
	☐	DALI	☐	Bluetooth
	☐	DMX	☐	Casambi
IP:		40		

Images / 3D / sections and the relative details shown in the following pages are generic and indicative. The number and position of the fixing points and fasteners may change during the production phase. The type, quantity and position of the Folio panels' power cables are indicative.

SLIM.9U

FOLIO

Product type	Quantity	1 Power	2 Screen type	3 CCT	4 Lens	5 Dimmability	6 Aluminum finish
SLIM.9U							

FINISH


6

Standard:

black ☐ white ☐

LENS INFO

Beam Angle (BA°): 120° ☐ 180° ☐




INSTALLATION

Magnetic

1. Secure the metal plate to the mounting surface


2. Magnetically attach the linear profile




POWER CABLE EXIT

Power cable: 1000 mm / 39 in


OPTION .A
EXIT FROM THE END CAP



OPTION .B
EXIT FROM THE SIDE




OPTION .C
EXIT FROM BELOW




POSITION GUIDELINES


OPTION .A



OPTION .B



OPTION .C



Images / 3D / sections and the relative details shown in the following pages are generic and indicative. The number and position of the fixing points and fasteners may change during the production phase. The type, quantity and position of the Folio panels' power cables are indicative.